

The 200S-50 concrete tie is a high performance, cost effective alternative for mainline and industrial track construction. The cost to build new track with concrete ties is very competitive with wood tie track, with lower installation cost, improved performance and substantially reduced maintenance costs.

200S-50 Tie Specifications

- **Elastic Fastener System:** Safelok III
- **Design Weight:** 700 lbs
- **Length:** 8' 6"
- **Flexural Strength:**
 - Railseat positive 319 in-kips
 - Center negative 218 in-kips
- **Tie Spacing:** Meets AREMA structural performance criteria for tie spacing from 24" to 28" on center
- **Concrete:** 7,000 psi minimum 28 day compressive strength with air entrainment
- **Pad:** 7.5mm 3-part pad
- **Rail Seat Cant:** 1:40
- **Rail Section:** 141 lb rail or other 6" base rail sections

The 200S-50 tie is designed for use with Safelok III fastening components. These components are chosen for their performance, cost and ease of installation.

Life Cycle Cost Savings

Easier installation, fewer required ties per track mile, greater life expectancy and reduced maintenance equals substantial life cycle cost savings.



Tie used on a industrial line



Efficient installation using hydraulic clamp

Proven Performance

CXT Concrete Ties has successfully supplied over 14 million concrete ties to the North American market.



800.790.2292
www.lbfoster.com

Mark Hammons - National Sales Mgr.
P: 509.921.8726 / M: 509.979.6891

Chuck Parks - Territory Sales Mgr.
P: 509.921.8736 / M: 509.209.1624



Spokane, Washington Facility

Benefits

- **Ease of Installation:** Our concrete ties, with a pre-set gauge, can be installed at rates of up to 1,200 ties per day.
- **Greater Efficiency:** Fewer concrete ties per track mile are required versus timber or other types of ties.
- **Greater Life Expectancy:** Concrete ties outlast other types of ties.
- **Reduced Maintenance:** Stiffer foundation for the entire track system will reduce required lining and surfacing maintenance and provides accurate track gauge.
- **Greater Fuel Economy:** Less friction and stiffer track structure allow rolling stock to move with less resistance, providing less fuel consumption.
- **Environmentally Safe:** Concrete ties contain no hazardous chemicals to harm the environment.
- **Excellent Gauge Holding:** Elastic fastening system increases resistance to longitudinal rail movement developed by thermal stress and traffic loads.
- **Safety:** Limited lateral and longitudinal movement of rail reduces derailments and minimizes derailment damage.